

# Product specifications

New Pam Series P - HT is a 3D printer dedicated to the manufacturing of performance thermoplastic parts using industrial injection molding pellets and your proprietary chemistries (formulations, blends, compounds). It is the most versatile 3D printer enabling to handle the widest variety of materials to create functional prototypes, toolings and small and medium scale series.

- Full setup control
- Performance thermoplastics
- High temperature solutions
- Multi-material & Multi-resolution
- Modular solution
- TPEs from Shore 00 to Shore D

<b>General specifications</b>	3D printing process	Pellet Additive Manufacturing (PAM)
	Number of extruder	2
	Physical Dimensions	Ø 834 x H 925 mm - 95 kg
	Maximum print volume	Ø300 * H300 mm (no radiant disc). Ø270 * H300 mm (with radiant disc)
	Power	3 500 W
	Power requirements	230 V ~ 8 A - 50Hz - IEC 60320 type C20
<b>Print head</b>	Nozzles sizes	Ø 0.25 - 0.30 - 0.40 - 0.60 - 0.80 - 1.00 - 1.20 mm
	Printing resolution (layer height)	40 µm - 1.2 mm
	Maximum extrusion temperature	450°C
	Maximum print bed temperature	150°C - 250 °C in option
	Maximum heating room temperature	70°C
	Maximum local radiant disc temperature	300°C
<b>Materials</b>	Grades	Injection molding pellet materials
	Compatible materials	Performance thermoplastics, TPEs Fillers: fiber, mineral, natural
	Maximum viscosity	6 000 Pa.s at negligible shear and process temperature
	Granulometry	Head cutting, cold cutting
	Pellet size	2 - 4 mm
	Supplier	Open
<b>Software</b>	CAD solution	Open (not supplied)
	Slicing	Cura by Pollen AM
	Control software	HoneyPrint
	Network communication	Ethernet protocol

## No special facilities needed

You can install a Pam 3D Printer just about anywhere.  
No access to gas, air or fluid required.

## Pollen AM Headquarter

19 rue Marceau  
FR-94200 Ivry-sur-Seine  
France  
+33 (0)1 58 46 20 52  
[contact@pollen.am](mailto:contact@pollen.am)

